

INDICATOR 3200

Weight indicator with extended scale functions

BENEFITS

- Code entry, kg/lb toggle
- Relay for automatic dosing
- Display with backlight
- Internal clock for date/time
- For warehousing, dosing and mixing
- Bluetooth 4.0 for RAVAS WeightsApp



Top quality

Advanced functions



FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare by push button
- Tare entry by cursor function
- Totaling with sequence number
- Code entry for max. 5-digit codes, by cursor function
- Three data output modes: print, continuous and command/answer
- kg or lb toggle
- Internal clock (for recording date/time on printout)
- Error messages in display
- Power supply to printer switched on and off by indicator
- Automatic shut-off function, defined by parameter setting
- Low battery indication
- Bluetooth 4.0 for RAVAS WeightsApp

STANDARD SPECIFICATIONS

- | | |
|---------------------|--|
| ▪ Display | digital |
| ▪ Segments | LCD, digit height 20 mm, backlight, dual color |
| ▪ Graduation | 0,1, 0,2, 0,5, 1, 2, 5, 10, 20 or 50 kg (see specifications weighing system) |
| ▪ Housing | plastic (ABS) |
| ▪ Bracket | steel |
| ▪ Colour | red (RAL 3000) |
| ▪ Protection class | IP65 / NEMA 4 |
| ▪ Power supply | 12V (230V for stationary applications) |
| ▪ Power consumption | 100 mA |
| ▪ Dimensions | exc. bracket: 60 x 77 x 182 mm |



OPTIONS*

- Printer output to thermal or matrix printer
- Bluetooth 2.0 or WLAN output
- Relay setpoint switch, for automatic dosing
- RS232 output for cable connection to truck terminal
- Multirange graduation (see specifications weighing system)
- Explosion proof version (Exd) (expected 2nd half of 2020)
- RDC, RAVAS Data Collector Software
- RIS, RAVAS Integration Software

RAVAS Europe B.V.

Toepadweg 7, 5301 KA Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

RAVAS